

Rubber Fab

a Garlock Hygienic Technologies company

RFFDAE



Food Grade FDA EPDM Rubber Hose

TUBE: Smooth white EPDM

COVER: Grey EPDM rubber

REINFORCEMENT: Two polyester spirals with dual helix wire

TEMPERATURE: -20°F to 300°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
08RFFDAE	0.50	0.97	1.50	300	FULL	0.30
12RFFDAE	0.75	1.27	2.50	300	FULL	0.44
16RFFDAE	1.00	1.50	3.00	300	FULL	0.57
24RFFDAE	1.50	2.09	4.50	300	FULL	0.91
32RFFDAE	2.00	2.63	6.00	250	FULL	1.30
40RFFDAE	2.50	3.17	8.00	200	FULL	1.74
48RFFDAE	3.00	3.72	10.00	200	FULL	2.42
64RFFDAE	4.00	4.78	14.00	150	FULL	3.22
96RFFDAE	6.00	6.79	28.00	100	FULL	5.35

Features

- Smooth inner bore
- Will not impart taste or odor
- Full vacuum
- Abrasion resistant
- Chemical and ozone resistant
- Static grounding available

Applications

- Sanitary suction and discharge
- Hot air blower service for food applications
- Food and beverage transfer
- Dairy
- CIP pharmaceutical
- Non-fatty and non-oily food products

Hose Certifications

- FDA 21 CFR 177.2600
- 3-A Sanitary Standards
- USDA
- Conforms to the construction criteria of the Grade A Pasteurized Milk Ordinance



26 Brookfield Drive • Sparta, New Jersey 07871

973.579.2959 • 866-442-2959 Toll Free • 973.579.7275 Fax • www.rubberfab.com