

Rubber Fab

a Garlock Hygienic Technologies company

Distributed by:

Tri-Canada

1000 Edgeley Blvd. #2, Vaughan, ON L4K 4V4
Tel: **905.677.9000** • Toll Free: **1.800.486.7863**
www.tricanada.com

RFRT



*Smoothbore FEP Lined EPDM
Rubber Covered Hose*

TUBE: Seamless white FEP

COVER: EPDM rubber (abrasion resistant)

REINFORCEMENT: Multiple braids,
helical wire

TEMPERATURE: -40°F to 300°F

Part Number	Hose ID Inch	Hose OD Inch	Bend Radius Inch	Max. Working Pressure @ 70°F psig	Vacuum Rating @ 70°F in. Hg.	Weight Per Foot
08RFRT	0.50	0.97	2.50	500	FULL	0.35
12RFRT	0.75	1.27	2.50	500	FULL	0.52
16RFRT	1.00	1.48	3.00	400	FULL	0.55
24RFRT	1.50	2.04	4.50	350	FULL	0.87
32RFRT	2.00	2.54	7.00	300	FULL	1.17
40RFRT	2.50	3.04	9.00	200	FULL	1.55
48RFRT	3.00	3.81	35.00	200	FULL	2.98
64RFRT	4.00	4.89	20.00	150	FULL	3.98

Features

- EPDM rubber outer cover has multiple textile plies along the entire length
- Double steel wire helix for improved bend radius and shape retention
- Liner is smooth FEP, bonded for full vacuum service
- Non-stick contact surface will not contaminate product
- Inert and resistant to most chemicals and reagents
- Cleanable by CIP, COP methods
- Ultra smooth bacteria free tube
- Static grounding available

Applications

- Pharmaceutical processing
- Water, acid, and chemical transfer
- Hot CIP solutions
- Distillery piping systems
- Electronic industries
- Fluid transfer
- Food and beverage processing
- Load cells
- Cosmetics

Hose Certifications

- Meets USP Class VI Standards
- FDA 21 CFR 177.1550
- FDA 21 CFR 177.2600
- 3-A Sanitary Standards

